




US SEALED SERIES

For DEVICE Type1

Housing (UNIT : mm) * For terminal selection, please contact our sales staff.

Terminal (UNIT : mm)


1.5 (S)



F (8100-4379)

Applicable wire size (mm ²)	0.35-0.5 AWG22-20
Cable overall diameter (mm)	1.7-1.9
Material	Heat-resistant copper alloy
Surface treatment	Sn plated
Applicable Tab Thickness (mm)	0.8


1.5 (M)



F (8100-4377)

Applicable wire size (mm ²)	0.8-1.0 AWG18-16
Cable overall diameter (mm)	2.2-2.4
Material	Heat-resistant copper alloy
Surface treatment	Sn plated
Applicable Tab Thickness (mm)	0.8


0.64 3way



F (6189-1024) key-K note)

Ref:Terminal part No.	P3
Material	PBT
Color	Yellow


0.64 4way



F (6189-7011) key-A note)

Ref:Terminal part No.	P3
Material	PBT
Color	Black


0.64 4way



F (6189-1019) key-E note)

Ref:Terminal part No.	P3
Material	PBT
Color	Yellow


0.64 5way



F (6189-7001) key-E note)

Ref:Terminal part No.	P3
Material	PBT
Color	Yellow


0.64 5way



F (6189-6936) key-K note)

Ref:Terminal part No.	P3
Material	PBT
Color	Yellow


0.64 5way



F (6189-7199) key-B note)

Ref:Terminal part No.	*
Material	PBT
Color	Black


1.5 4way



F (6189-6897) note)

Ref:Terminal part No.	P18
Ref:Wire seal No.	P17
Material	PBT
Color	Black

F Back TPA (6185-4630)



Material	PBT
Color	Gray