

US SEALED SERIES

For DEVICE Type2

Terminal (UNIT : mm)


2.8 (S) Sn



F (8240-0428)

Applicable wire size (mm ²)	0.5-1.0 AWG20-18
Cable overall diameter (mm)	1.9-2.2
Material	Heat-resistant copper alloy
Surface treatment	Sn plated
Applicable Tab Thickness (mm)	0.8

2.8 (M) Sn



F (8240-0429)

Applicable wire size (mm ²)	1.5-2.5 AWG16-14
Cable overall diameter (mm)	2.4-2.7
Material	Heat-resistant copper alloy
Surface treatment	Sn plated
Applicable Tab Thickness (mm)	0.8

2.8 (L) Sn



F (8240-0430)

Applicable wire size (mm ²)	3.0-4.0 AWG12
Cable overall diameter (mm)	3.3
Material	Heat-resistant copper alloy
Surface treatment	Sn plated
Applicable Tab Thickness (mm)	0.8


2.8 (S) Grease



F (8240-0431)

Applicable wire size (mm ²)	0.5-1.0 AWG20-18
Cable overall diameter (mm)	1.9-2.2
Material	Heat-resistant copper alloy
Surface treatment	Sn plated
Applicable Tab Thickness (mm)	0.8


2.8 (S) Ag



F (8240-0434)

Applicable wire size (mm ²)	0.5-1.0 AWG20-18
Cable overall diameter (mm)	1.9-2.2
Material	Heat-resistant copper alloy
Surface treatment	Ag plated
Applicable Tab Thickness (mm)	0.8


2.8 (M) Grease



F (8240-0432)

Applicable wire size (mm ²)	1.5-2.5 AWG16-14
Cable overall diameter (mm)	2.4-2.7
Material	Heat-resistant copper alloy
Surface treatment	Sn plated
Applicable Tab Thickness (mm)	0.8


2.8 (M) Ag



F (8240-0435)

Applicable wire size (mm ²)	1.5-2.5 AWG16-14
Cable overall diameter (mm)	2.4-2.7
Material	Heat-resistant copper alloy
Surface treatment	Ag plated
Applicable Tab Thickness (mm)	0.8


2.8 (L) Grease



F (8240-0433)

Applicable wire size (mm ²)	3.0-4.0 AWG12
Cable overall diameter (mm)	3.3
Material	Heat-resistant copper alloy
Surface treatment	Sn plated
Applicable Tab Thickness (mm)	0.8


2.8 (L) Ag



F (8240-0436)

Applicable wire size (mm ²)	3.0-4.0 AWG12
Cable overall diameter (mm)	3.3
Material	Heat-resistant copper alloy
Surface treatment	Ag plated
Applicable Tab Thickness (mm)	0.8


1.5 2way



F (6189-7171) key-A note)

Ref.Terminal part No.	*
Material	PBT
Color	Black


2.8 2way



F (6189-7290) key-A

Ref.Terminal part No.	P19
Material	PBT
Color	Black


2.8 2way



F (6189-7373) key-B

Ref.Terminal part No.	P19
Material	PBT
Color	Black


2.8 2way



F (6189-7374) key-C

Ref.Terminal part No.	P19
Material	PBT
Color	Black


2.8 3way



F (6189-7291) key-A

Ref.Terminal part No.	P19
Material	PBT
Color	Black


2.8 3way



F (6189-7375) key-B

Ref.Terminal part No.	P19
Material	PBT
Color	Black

2.8 4way



F (6189-7292) key-A

Ref.Terminal part No.	P19
Material	PBT
Color	Black